

AXC -114 SOLARIS RED
Waterborne Basecoat System

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** AXC -114 SOLARIS RED
Waterborne Basecoat System
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Liquid paint. For industrial user only.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
CROMAUTO COATINGS, S.L.U.
C/ Artapadura 7 B Nave 37
01013 Vitoria-Gasteiz - Araba - España
Phone.: +34 937494502 - Fax: +34 938646076
info@cromauto.com
http://www.cromauto.com
- 1.4 Emergency telephone number:** +34 937494502 (8:00-13:00) (14:30-17:30)

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
The product is not classified as hazardous according to CLP Regulation (EC) No 1272/2008.
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Hazard statements:
Non-applicable
Precautionary statements:
Non-applicable
Supplementary information:
EUH208: Contains 2-methylisothiazol-3(2H)-one. May produce an allergic reaction
EUH210: Safety data sheet available on request
- 2.3 Other hazards:**
Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

- 3.1 Substance:**
Non-applicable
- 3.2 Mixture:**
Chemical description: Aqueous mixture composed of additives, coalescents, pigments and resins

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 111-76-2 EC: 203-905-0 Index: 603-014-00-0 REACH: 01-2119475108-36-XXXX	2-butoxyethanol <input type="checkbox"/> ¹ <input type="checkbox"/> Regulation 1272/2008 Acute Tox. 4: H302+H312+H332; Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Warning	ATP CLP00 5 - <10 %

¹ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

- 4.1 Description of first aid measures:**

- CONTINUED ON NEXT PAGE -

**AXC -114 SOLARIS RED
Waterborne Basecoat System**

SECTION 4: FIRST AID MEASURES (continued)

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. IT IS NOT RECOMMENDED to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

- CONTINUED ON NEXT PAGE -

**AXC -114 SOLARIS RED
Waterborne Basecoat System**

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C
Maximum Temp.: 30 °C
Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace

Identification		Environmental limits	
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	IOELV (8h)	20 ppm	98 mg/m ³
	IOELV (STEL)	50 ppm	246 mg/m ³

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	89 mg/kg	Non-applicable	75 mg/kg	Non-applicable
	Inhalation	663 mg/m ³	246 mg/m ³	98 mg/m ³	Non-applicable

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	Oral	13,4 mg/kg	Non-applicable	3,2 mg/kg	Non-applicable
	Dermal	44,5 mg/kg	Non-applicable	38 mg/kg	Non-applicable
	Inhalation	426 mg/m ³	123 mg/m ³	49 mg/m ³	Non-applicable

PNEC:

- CONTINUED ON NEXT PAGE -

AXC -114 SOLARIS RED
Waterborne Basecoat System

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
2-butoxyethanol	STP	463 mg/L	Fresh water	8,8 mg/L
CAS: 111-76-2	Soil	3,13 mg/kg	Marine water	0,88 mg/L
EC: 203-905-0	Intermittent	9,1 mg/L	Sediment (Fresh water)	34,6 mg/kg
	Oral	20 g/kg	Sediment (Marine water)	Non-applicable

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Non-applicable

D.- Ocular and facial protection

Non-applicable

E.- Body protection

Non-applicable

F.- Additional emergency measures

It is not necessary to take additional emergency measures.

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	10,07 % weight
V.O.C. density at 20 °C:	108,8 kg/m ³ (108,8 g/L)
Average carbon number:	5,91
Average molecular weight:	116,95 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Viscous
Colour:	Red
Odour:	Soft
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	106 °C
Vapour pressure at 20 °C:	2298 Pa
Vapour pressure at 50 °C:	12109,76 Pa (12,11 kPa)
Evaporation rate at 20 °C:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

**AXC -114 SOLARIS RED
Waterborne Basecoat System**

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Product description:

Density at 20 °C:	1060 - 1100 kg/m ³
Relative density at 20 °C:	1,06 - 1,1
Dynamic viscosity at 20 °C:	366 - 260 cP
Kinematic viscosity at 20 °C:	290 cSt
Kinematic viscosity at 40 °C:	>20,5 cSt
Concentration:	Non-applicable *
pH:	8,4 - 8,8
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Miscible
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *

Flammability:

Flash Point:	Non Flammable (>60 °C)
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	238 °C
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *

Explosive:

Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *

9.2 Other information:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Not applicable	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

- CONTINUED ON NEXT PAGE -

AXC -114 SOLARIS RED
Waterborne Basecoat System

SECTION 10: STABILITY AND REACTIVITY (continued)

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
IARC: 2-butoxyethanol (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

- CONTINUED ON NEXT PAGE -

**AXC -114 SOLARIS RED
Waterborne Basecoat System**

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Specific toxicology information on the substances:

Identification		Acute toxicity		Genus
2-butoxyethanol	LD50 oral	1414 mg/kg		Rat
CAS: 111-76-2	LD50 dermal	1060 mg/kg		Rabbit
EC: 203-905-0	LC50 inhalation	11 mg/L (4 h)		Rat

Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity	
Oral	14665,4 mg/kg (Calculation method)	0 %	
Dermal	10993,87 mg/kg (Calculation method)	0 %	
Inhalation	109,2 mg/L (4 h) (Calculation method)	0 %	

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification		Acute toxicity		Species	Genus
2-butoxyethanol	LC50	1490 mg/L (96 h)		Lepomis macrochirus	Fish
CAS: 111-76-2	EC50	1815 mg/L (48 h)		Daphnia magna	Crustacean
EC: 203-905-0	EC50	911 mg/L (72 h)		Pseudokirchneriella subcapitata	Algae

12.2 Persistence and degradability:

Identification		Degradability		Biodegradability	
2-butoxyethanol	BOD5	0.71 g O2/g	Concentration	100 mg/L	
CAS: 111-76-2	COD	2.2 g O2/g	Period	14 days	
EC: 203-905-0	BOD5/COD	0.32	% Biodegradable	96 %	

12.3 Bioaccumulative potential:

Identification		Bioaccumulation potential	
2-butoxyethanol	BCF		3
CAS: 111-76-2	Pow Log		0.83
EC: 203-905-0	Potential		Low

12.4 Mobility in soil:

Identification		Absorption/desorption		Volatility	
2-butoxyethanol	Koc	8	Henry	1,621E-1 Pa·m ³ /mol	
CAS: 111-76-2	Conclusion	Very High	Dry soil	No	
EC: 203-905-0	Surface tension	2,729E-2 N/m (25 °C)	Moist soil	Yes	

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 12	waste paint and varnish other than those mentioned in 08 01 11	Non dangerous

Type of waste (Regulation (EU) No 1357/2014):

Non-applicable

Waste management (disposal and evaluation):

- CONTINUED ON NEXT PAGE -

**AXC -114 SOLARIS RED
Waterborne Basecoat System**

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommend disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains 2-methylisothiazol-3(2H)-one.

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled

Eye Irrit. 2: H319 - Causes serious eye irritation

Skin Irrit. 2: H315 - Causes skin irritation

Classification procedure:

- CONTINUED ON NEXT PAGE -

AXC -114 SOLARIS RED
Waterborne Basecoat System

SECTION 16: OTHER INFORMATION (continued)

Non-applicable

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient

Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -