


# **TECHNICAL DATA SHEET**



# **ELAST 101**

POLYESTER PUTTY FOR PLASTICS



# **PRODUCTS**

ELAST 101 GRIS

## **PROPERTIES**

- Specially for repairing plastics Especial PC, PC-PBT, PP-EPDM.
- Noted for its easy application.
- Great filling for cracks and scratches.
- Excellent sanding and superb finishes.

# **SUBSTRATES**

- Product especially designed for repairing plastics.
- The use of FILLER 220-225-229-250 is recommended.





# ELAST 101 POLYESTER PUTTY FOR PLASTICS

# **PRODUCT PREPARATION**

		Horizontal panel or mid size reparations			
		Weight			
MIXING RATIO VOLUME	PEROXIDE	2-3%			
POT-LIFE AT 20°C	PEROXIDE	3-5 min.			
APPLICATION VISCOSITY AT 20°C	FORD N°	No			
	SPRAY GUN HLVP	Nozzle	Distance	Pressure	
APPLICATION EQUIPMENT	SUCTION	NO	NO	NO	
	GRAVITY	NO	NO	NO	
NR LAYERS	No				
THINNER	No				
DFT	1000-3000 microns				
DI I	Peroxide				
	DRY	30 min.			
DRYING TIME	JULI SU IIIII.				
IR	EVAPORATION TIME	5 min.			
INFRARED DRYING	MIDDLE WAVE	P80-P120			





POLYESTER PUTTY FOR PLASTICS



### **SURFACE PREPARATION**

- Wash the surface with soap and water. Rinse and dry.
- Remove grease thoroughly with proper cleanser. Dry surface with clean cloth.
- Repair damages.
- Degrease using proper cleansing product. Dry with clean cloth.
- Make sure there are not any traces of dust.
- If necessary, apply a double-coating base.

### **STORAGE**

Store products under cover, in a well-ventilated area, away from direct sun-light. Store at temperatures between 5-30 degrees Celsius.

Duration of container 2 years. After that period, please consult our technical department.

## **HEALTH AND SAFETY**

For Professional use Only.

KEEP AWAY FROM CHILDREN. WARNING! FLAMMABLE CONTENT.

HARMFUL VAPORS AND VOLATILE COMPOUNDS. IRRITATING TO EYES AND SKIN.

Handle CROMAUTO products only after having read and understood completely the materials security and safety information data sheets. Make sure that every employee is aware of data information sheets as well as all the chemical substances they get in contact with. The Manufacturer recommends the use of an air respirator while being exposed to the sprayed mist and vapors. Use appropriate clothing, gloves, and goggles with side shields.

The information provided in these sheets is given in good faith, but it does not constitute a guarantee. The included information represents our current knowledge and it is aimed to serve as a guide or reference of our products and their purpose, but it does not guarantee certain properties of the products nor their specific applications.

Please, respect every warning on the products labels.