

MULTI 150

POLYESTER MULTIFUNCIONAL PUTTY

Polyester putty with high adhesion and filling power.

PRODUCTS

MULTI 150

PROPERTIES

- Intended to fill dents and other irregularities in the vehicle body.
- Noted for its adherence.
- Excellent filling power and flexibility.
- Usable for painting cars and commercial vehicles.









SUBSTRATES

- Perfect adhesion to galvanized and zinc plated steel.
- We recommend the use of FILLER 220-225-229-250.

MULTI 150

POLYESTER MULTIFUNCIONAL PUTTY

PRODUCT PREPARATION

 MIXING RATIO VOLUME		Horizontal panel or mid size reparations
	PEROXIDE	Weight 2-3%
 POT-LIFE AT 20°C	PEROXIDE	3-5 min.
 APPLICATION VISCOSITY AT 20°C	FORD N°	No
 SPATULA APPLICATION		Spatula application
 NR LAYERS		No
 THINNER EVAPORATION		No
DFT		1000-3000 microns
 DRYING TIME		Peroxide
	DRY	30 min.
 INFRARED DRYING	MIDDLE WAVE	5 min.
	SANDING	P80-P180

MULTI 150

POLYESTER MULTIFUNCIONAL PUTTY

SURFACE PREPARATION

- Wash the surface with soap and water. Rinse and dry.
- Remove grease thoroughly with proper cleanser. Dry surface with clean cloth.
- Repair damages.
- Degrease using proper cleansing product. Dry with clean cloth.
- Make sure there are not any traces of dust.
- If necessary, apply a double-coating base.

STORAGE

Store product under cover, in a well-ventilated area, away from direct sun-light. Store at temperature between 5-30 degrees Celsius.

Duration of container 2 years. After that period, please consult our technical department.

HEALTH AND SAFETY

For Professional use Only.

KEEP AWAY FROM CHILDREN. WARNING! FLAMMABLE CONTENT.

HARMFUL VAPORS AND VOLATILE COMPOUNDS. IRRITATING TO EYES AND SKIN.

Handle CROMAUTO products only after having read and understood completely the materials security and safety information data sheets. Make sure that every employee is aware of data information sheets as well as all the chemical substances they get in contact with. The Manufacturer recommends the use of an air respirator while being exposed to the sprayed mist and vapors. Use appropriate clothing, gloves, and goggles with side shields.

The information provided in these sheets is given in good faith, but it does not constitute a guarantee. The included information represents our current knowledge and it is aimed to serve as a guide or reference of our products and their purpose, but it does not guarantee certain properties of the products nor their specific applications.

Please, respect every warning on the products labels.